

MULTI SOCKET OUTLETS

Standard construction for 19" RACK / 1Unit



Multi socket outlet 19" RACK, 1 Unit


- for universal installation in 19" (48.26 cm) network cabinets or IT server racks
- sturdy plastic or aluminium housing in standardised construction
- Shock-proof socket outlets with earthing contact and increased contact protection in 45° arrangement
- Height (rack unit): 1U (44.45 mm)
- 230 V~ / 16 A / max. 3500 W*
- IP20: For indoor use



Fig.	Version	Connection	Housing	EAN	Art. no.
1	8-way*	3 m PVC cable H05V-F 3G1.5 With shock-proof angle plug	Plastic, black	4011160181900	18190
2	8-way* with illuminated on/off switch	3 m PVC cable H05V-F 3G1.5 With shock-proof angle plug	Plastic, black	4011160181917	18191
3	8-way with overload protection 10 A with reset function, 230 V~ / 10 A / max. 2300 W	3 m PVC cable H05V-F 3G1.5 with type C14 IEC cold-device plug	Plastic, black	4011160181924	18192
4	8-way* U _c : 250 V~ 50 Hz Typ3, U _{oc} : 6.0 KV (L-N, L/N-PE) Up: 2.0 KV (L/N-PE); 1.8 KV (L-N)	2 m PVC cable H05V-F 3G1.5 With shock-proof angle plug	Aluminium, black	4011160181931	18193
5	9-way*	2 m PVC cable H05V-F 3G1.5 With shock-proof angle plug	Aluminium, black	4011160181948	18194



Various
mounting angles possible.



without power cord




Mounting clip for
each side



Various
plug-in options
for clips



Connection
space with
cover



Connection up to
max. 3G1.5

Examples for fixing the mounting clips at different angles.



Multi-angle socket outlet 19" RACK, 1 Unit

- for universal installation in 19" (48.26 cm) network cabinets or IT server racks
- enclosed, lateral mounting clips can be placed horizontally, vertically and in 30° positions
- sturdy aluminium housing in standardised construction
- 7 shock-proof socket outlets with increased contact protection in 45° arrangement
- Multi socket outlet with large connection space for self-assembly of a cable up to max. 3G1.5 (cable not included in scope of delivery)
- with illuminated on/off switch
- Height (rack unit): 1U (44.45 mm)
- 230 V~ / 16 A / max. 3500 W
- IP20: For indoor use



Version	Connection	Housing	EAN	Art. no.
7-way with illuminated on/off switch	with large connection space for self-assembly of a cable	Aluminium, black	4011160181955	18195



MULTI SOCKET OUTLETS

in standard construction for 19" RACK / 1 Unit

Server, switch, storage, controller and back-up systems. These are just a few components that can be installed in an **IT cabinet**. If a **large number of devices** are installed in a rack, numerous **connection options to the power** are required.

With our 19" multi socket outlets, **up to nine devices can be connected** to one power connection via earthing contact plugs. The standard construction makes it **easy to install in the profile rails** of your 19 inch rack.

You can choose from **different models**. For more safety, we also offer multi socket outlets with integrated surge or overload protection.

- ✓ Suitable for installation in **19 inch cabinets/racks (48.26 cm)**
- ✓ Suitable for **telephone systems, network distributors and servers**, among others
- ✓ Various models with **switch, surge protection or overload protection**
- ✓ **HIGHLIGHT:** Multi-angle socket outlet for maximum installation flexibility



Sturdy housing
made of plastic or aluminium

1 Unit ≈ 44.45 mm

Your partner for professional lighting and electrical products

as - Schwabe GmbH | Merkurstraße 10 | D - 72184 Eutingen | Tel. +49 7457 9 48 53 10 | d.mueck@as-schwabe.de | www.as-schwabe.de

7/2021. Errors and modifications reserved. Reproduction only with the authorisation of as - Schwabe GmbH.

as[®]
Schwabe
TechnikProdukte