Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources					
Supplier's name	e or trade mark:	as - Schwabe			
Supplier's addre	ess: Produktman	agement, Merkursti	r. 10, 72184 Eutingen im	Gäu, DE	
Model identifie	r: 46268				
Type of light so	urce:				
Lighting technol	logy used:	other	Non-directional or directional:	DLS	
Light source cap	o-type	-			
(or other electri	ic interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein	
Colour-tuneable	e light source:	Nein	Envelope:	-	
High luminance	light source:	Nein			
Anti-glare shield:		Nein	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
_		General product p		_	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		400	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		35 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P _{on}), expressed in W		400,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85	
Outer	Height	-	Spectral power	See image	
dimensions without	Width	-	distribution in the	in last page	
without	Depth	-			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-			
	Chromaticity coordinates (x and y)	-			
Parameters for directional light sources:					
Peak luminous intensity (cd)	- Beam angle in degrees, or the range of beam angles that can be set				

(a)'-': not applicable; (b)'-': not applicable;