## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: as - Schwabe

Supplier's address: Produktmanagement, Merkurstr. 10, 72184 Eutingen im Gäu, DE

## Model identifier: 46370

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	-				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	No		
Product parameters					

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
• ·	nption in on- 100 h), rounded st integer	70	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	6 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode p expressed in W	oower (P <sub>on</sub> ),	-	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	_		
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions	Height	-	Spectral power	See image		
	Width	-	distribution in the	in last page		
without	Depth	-	1	Seite 1 / 2		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,304 0,314			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,00			
the lumen maintenance factor	0,97					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;